



## NutLink V Belts

Belt	Colour	Compliance	Material	Temperature Range		Roll Length (m)	Weight
				°F	°C		kg/m
<b>NuTlink-Z</b>	Orange	ROHS	Composite Polyester/ Polyurethane Steel Rivets	-40 to +240	-40 to +116	20	0.10
<b>NuTlink-A</b>	Orange	ROHS	Composite Polyester/ Polyurethane Steel Rivets	-40 to +240	-40 to +116	20	0.15
<b>NuTlink-B</b>	Orange	ROHS	Composite Polyester/ Polyurethane Steel Rivets	-40 to +240	-40 to +116	20	0.20

\*All sizes are available for purchase / mtr

# EAGLE® Polyurethane Belting

## Eagle Green 89 Textured

Size	Dimensions (mm)	Minimum Pulley Ø (mm)	Working Load @ percent Tension								Weight
			4%		6%		8%		10%		kg/m
			lbs	N	lbs	N	lbs	N	lbs	N	
<b>PC-4R</b>	4	36	0.9	4.1	1.5	6.8	2.1	9.3	2.6	11.6	0.015
<b>PC-5R</b>	5	45	1.5	6.5	2.4	10.6	3.3	14.6	4.1	18.2	0.023
<b>PC-6R</b>	6	54	2.1	9.3	3.4	15.3	4.7	21	5.9	26.2	0.034
<b>PC-8R</b>	8	72	3.7	16.6	6.1	27.2	8.4	37.3	10.5	46.7	0.06
<b>PC-10R</b>	10	90	5.8	25.8	9.5	42.3	13.1	58.1	16.3	72.5	0.093
<b>PC-12R</b>	12	108	8.4	37.3	13.8	61.2	18.9	84.1	23.6	105.1	0.135

\*All sizes are available for purchase / mtr

All above sizes are kept in stock at Finer Power Transmissions - other sizes and variations are available on request.