






Glacier Bushes

GLACIER BUSHES

DU Imperial Cylindrical Bushes	8.2.4
DU Metric Cylindrical Bushes	8.2.6
DX Imperial Cylindrical Bushes (Lined)	8.2.10
DX Metric Cylindrical Bushes (Lined)	8.2.10




DU Imperial Cylindrical Bushes



Unit: Inch

Part No.	Nominal Diameter		L +0.010 -0.010	ID After Fitted	Housing Bore (H7)	Shaft Dia (f7)	f1	f2
	d	D						
IB02DU03	1/8	3/16	3/16	0.1268	0.1878	0.1243	0.5±0.3	0.25±0.2
				0.1243	0.1873	0.1236	0.5±0.3	
IB03DU06	3/16	1/4	3/8	0.1893	0.2503	0.1865	0.5±0.3	0.25±0.2
				0.1867	0.2497	0.1858	0.5±0.3	
IB04DU06	1/4	5/16	3/8	0.2518	0.3128	0.2490	0.5±0.3	0.25±0.2
				0.2492	0.3122	0.2481	0.5±0.3	
IB05DU06	5/16	3/8	3/8	0.3143	0.3753	0.3115	0.5±0.3	0.25±0.2
IB05DU08			1/2	0.3117	0.3747	0.3106	0.5±0.3	0.25±0.2
IB06DU06	3/8	15/32	3/8	0.3769	0.4691	0.3740	0.6±0.3	0.25±0.2
IB06DU12			3/4	0.3742	0.4684	0.3731	0.6±0.3	0.3±0.2
IB07DU08	7/16	17/32	1/2	0.4394	0.5316	0.4365	0.6±0.3	0.3±0.2
IB07DU12			3/4	0.4367	0.5309	0.4355		
IB08DU06	1/2	19/32	3/8	0.5019	0.5941	0.4990	0.6±0.3	0.3±0.2
IB08DU08			1/2				0.6±0.3	0.3±0.2
IB08DU10			5/8	0.4992	0.5934	0.4980	0.6±0.3	0.3±0.2
IB08DU12			3/4				0.6±0.3	0.3±0.2
IB08DU14			7/8				0.6±0.3	0.3±0.2
IB09DU08	9/16	21/32	1/2	0.5644	0.6566	0.5615	0.6±0.3	0.3±0.2
IB09DU12			3/4	0.5617	0.6559	0.5605	0.6±0.3	0.3±0.2
IB10DU10	5/8	23/32	5/8	0.6270	0.7192	0.6240	0.6±0.3	0.3±0.2
IB10DU12			3/4	0.6242	0.7184	0.6230	0.6±0.3	0.3±0.2
IB10DU14			7/8				0.6±0.3	0.3±0.2
IB12DU08	3/4	7/8	1/2	0.7525	0.8755	0.7491	0.7±0.3	0.5±0.2
IB12DU12			3/4	0.7493	0.8747	0.7479	0.7±0.3	0.5±0.2
IB12DU16			1				0.7±0.3	0.5±0.2
IB14DU16	7/8	1	1	0.8775	1.0005	0.8741	0.7±0.3	0.5±0.2
				0.8743	0.9997	0.8729	0.7±0.3	0.5±0.2
IB16DU6	1	1 1/8	3/8	1.0025	1.1255	0.9991	0.7±0.3	0.5±0.2
IB16DU12			3/4				0.7±0.3	0.5±0.2
IB16DU16			1	0.9993	1.1247	0.9979	0.7±0.3	0.5±0.2
IB16DU24			1.1/2				0.7±0.3	0.5±0.2
IB18DU08	1 1/8	1 9/32	1/2	1.1278	1.2818	1.1238	0.7±0.4	0.5±0.3
IB18DU16			1	1.1240	1.2808	1.1226	0.7±0.4	0.5±0.3





DU Imperial Cylindrical Bushes



Unit: Inch

Part No.	Nominal Diameter		L +0.010 -0.010	ID After Fitted	Housing Bore (H7)	Shaft Dia (f7)	f1	f2
	D	d						
IB20DU16	1.13/32	1 1/4	1	1.2528	1.4068	1.2488	0.7±0.4	0.5±0.3
IB20DU18			1.1/8					
IB20DU20			1.1/4					
IB20DU28			1.3/4					
IB22DU16	1.17*32	1 3/8	1	1.3778	1.5318	1.3738	0.7±0.4	0.5±0.3
				1.3740	1.5308	1.3722		
IB24DU16	1.21/32	1 1/2	1	1.5028	1.6568	1.4988	0.7±0.4	0.5±0.3
IB24DU20			1.1/4					
IB24DU24			1.1/2					
IB24DU32			2					
IB26DU24	1.25/32	1 5/8	1.1/2	1.6278	1.7818	1.6288	0.7±0.4	0.5±0.3
				1.6240	1.7808	1.6222		
IB28DU16	1.15/16	1 3/4	1	1.7535	1.9381	1.7487	1.8±0.6	0.5±0.3
IB28DU32			2					
IB30DU16	2.1/16	1 7/8	1	1.8787	2.0633	1.8737	1.8±0.6	0.6±0.3
IB30DU36			2.1/4					
IB32DU16	2.3/16	2	1	2.0037	2.1883	1.9987	1.8±0.6	0.6±0.3
IB32DU24			1.1/2					
IB32DU32			2					
IB32DU40			2.1/2					
IB36DU32	2.7/16	2 1/4	2	2.2573	2.4377	2.2507	1.8±0.6	0.6±0.3
				2.2509	2.4365	2.2489		
IB40DU48	2.11/16	2 1/2	3	2.5077	2.6881	2.5011	1.8±0.6	0.6±0.3
IB44DU32	2.15/16	2 3/4	2	2.7566	2.9370	2.7500	1.8±0.6	0.6±0.3
IB44DU56			3 1/2					
IB48DU32	3.3/16	3	2	3.0068	3.1872	3.0000	1.8±0.6	0.6±0.3
IB48DU48			3					
IB56DU40	3.11/16	3 1/2	2 1/2	3.5068	3.6872	3.5000	1.8±0.6	0.6±0.3
IB56DU60			3 3/4					
IB64DU32	4.3/16	4	2	4.0068	4.1872	4.0000	1.8±0.6	0.6±0.3
IB64DU48			3					
IB80DU48	5.3/16	5	3	5.0056	5.1860	4.9986	1.8±0.6	0.6±0.3
				4.9988	5.1844	4.9961		
IB96DU48	6.3/16	6	3	6.0070	6.1874	6.0000	1.8±0.6	0.6±0.3
				6.0002	6.1858	5.9975		

DU Metric Cylindrical Bushes



Unit: mm

Part No.	OD Tolerance	ID After Fitted	Wall Thickness	L +0.025 -0.025	Housing Bore (H7)	Shaft Dia (f7)	f1	f2			
MB0610DU	8	+0.055	6.055	1.005	10	8	+0.015	6	-0.010	0.6±0.3	0.3±0.2
		+0.025	5.990				0		-0.022		
MB0808DU	10	+0.055	8.055	1.005	8	10	+0.015	8	-0.013	0.6±0.3	0.3±0.2
		+0.025	7.990				0		-0.028		
MB0810DU	10	+0.055	8.055	1.005	10	10	+0.015	8	-0.013	0.6±0.3	0.3±0.2
		+0.025	7.990				0		-0.028		
MB0812DU	10	+0.055	8.055	1.005	12	10	+0.015	8	-0.013	0.6±0.3	0.3±0.2
		+0.025	7.990				0		-0.028		
MB1010DU	12	+0.065	10.058	1.005	10	12	+0.018	10	-0.013	0.6±0.3	0.3±0.2
		+0.030	9.990				0		-0.028		
MB1012DU	12	+0.065	10.058	1.005	12	12	+0.018	10	-0.013	0.6±0.3	0.3±0.2
		+0.030	9.990				0		-0.028		
MB1013.5DU	12	+0.065	10.058	1.005	13.5	12	+0.018	10	-0.013	0.6±0.3	0.3±0.2
		+0.030	9.990				0		-0.028		
MB1015DU	12	+0.065	10.058	1.005	15	12	+0.018	10	-0.013	0.6±0.3	0.3±0.2
		+0.030	9.990				0		-0.028		
MB1020DU	12	+0.065	10.058	1.005	20	12	+0.018	10	-0.013	0.6±0.3	0.3±0.2
		+0.030	9.990				0		-0.028		
MB1212DU	14	+0.065	12.058	1.005	12	14	+0.018	12	-0.016	0.6±0.3	0.3±0.2
		+0.030	11.990				0		-0.034		
MB1215DU	14	+0.065	12.058	1.005	15	14	+0.018	12	-0.016	0.6±0.3	0.3±0.2
		+0.030	11.990				0		-0.034		
MB1225DU	14	+0.065	12.058	1.005	25	14	+0.018	12	-0.016	0.6±0.3	0.3±0.2
		+0.030	11.990				0		-0.034		
MB1415DU	16	+0.065	14.058	1.005	15	16	+0.018	14	-0.016	0.6±0.3	0.3±0.2
		+0.030	13.990				0		-0.034		
MB1425DU	16	+0.065	14.058	1.005	25	16	+0.018	14	-0.016	0.6±0.3	0.3±0.2
		+0.030	13.990				0		-0.034		
MB1510DU	17	+0.065	15.058	1.005	10	17	+0.018	15	-0.016	0.6±0.3	0.3±0.2
		+0.030	14.990				0		-0.034		
MB1512DU	17	+0.065	15.058	1.005	12	17	+0.018	15	-0.016	0.6±0.3	0.3±0.2
		+0.030	14.990				0		-0.034		
MB1515DU	17	+0.065	15.058	1.005	15	17	+0.018	15	-0.016	0.6±0.3	0.3±0.2
		+0.030	14.990				0		-0.034		
MB1525DU	17	+0.065	15.058	1.005	25	17	+0.018	15	-0.016	0.6±0.3	0.3±0.2
		+0.030	14.990				0		-0.034		
MB1530DU	17	+0.065	15.058	1.005	30	17	+0.018	15	-0.016	0.6±0.3	0.3±0.2
		+0.030	14.990				0		-0.034		
MB1612DU	18	+0.065	16.058	1.005	12	18	+0.018	16	-0.016	0.6±0.3	0.3±0.2
		+0.030	15.990				0		-0.034		
MB1615DU	18	+0.065	16.058	1.005	15	18	+0.018	16	-0.016	0.6±0.3	0.3±0.2
		+0.030	15.990				0		-0.034		
MB1620DU	18	+0.065	16.058	1.005	20	18	+0.018	16	-0.016	0.6±0.3	0.3±0.2
		+0.030	15.990				0		-0.034		
MB1720DU	19	+0.075	17.061	1.005	20	19	+0.021	17	-0.016	0.6±0.3	0.3±0.2
		+0.035	16.990				0		-0.034		
MB1815DU	20	+0.075	18.061	1.005	15	20	+0.021	18	-0.016	0.6±0.3	0.3±0.2
		+0.035	17.990				0		-0.034		
MB1825DU	20	+0.075	18.061	1.005	25	20	+0.021	18	-0.016	0.6±0.3	0.3±0.2
		+0.035	17.990				0		-0.034		
MB2015DU	23	+0.075	20.071	1.505	15	23	+0.021	20	-0.020	0.7±0.3	0.5±0.3
		+0.035	19.990				0		-0.041		
MB2020DU	23	+0.075	20.071	1.505	20	23	+0.021	20	-0.020	0.7±0.3	0.5±0.3
		+0.035	19.990				0		-0.041		
MB2025DU	23	+0.075	20.071	1.505	25	23	+0.021	20	-0.020	0.7±0.3	0.5±0.3
		+0.035	19.990				0		-0.041		
MB2030DU	23	+0.075	20.071	1.505	30	23	+0.021	20	-0.020	0.7±0.3	0.5±0.3
		+0.035	19.990				0		-0.041		

DU Metric Cylindrical Bushes

Part No.	OD Tolerance	ID After Fitted	Wall Thickness	L +0.025 -0.025	Housing Bore (H7)	Shaft Dia (f7)	f1	f2		
MB2035DU	+0.075	20.071	1.505	35	23	+0.021	20	-0.020	0.7±0.3	0.5±0.3
	+0.035	19.990	1.475			0		-0.041		
MB2215DU	+0.075	22.071	1.505	15	25	+0.021	22	-0.020	0.7±0.3	0.5±0.3
	+0.035	21.990	1.475			0		-0.041		
MB2220DU	+0.075	22.071	1.505	20	25	+0.021	22	-0.020	0.7±0.3	0.5±0.3
	+0.035	21.990	1.475			0		-0.041		
MB2225DU	+0.075	22.071	1.505	25	25	+0.021	22	-0.020	0.7±0.3	0.5±0.3
	+0.035	21.990	1.475			0		-0.041		
MB2415DU	+0.075	24.071	1.505	15	27	+0.021	24	-0.020	0.7±0.3	0.5±0.3
	+0.035	23.990	1.475			0		-0.041		
MB2420DU	+0.075	24.071	1.505	20	27	+0.021	24	-0.020	0.7±0.3	0.5±0.3
	+0.035	23.990	1.475			0		-0.041		
MB2425DU	+0.075	24.071	1.505	25	27	+0.021	24	-0.020	0.7±0.3	0.5±0.3
	+0.035	23.990	1.475			0		-0.041		
MB2430DU	+0.075	24.071	1.505	30	27	+0.021	24	-0.020	0.7±0.3	0.5±0.3
	+0.035	23.990	1.475			0		-0.041		
MB2515DU	+0.075	25.071	1.505	15	28	+0.021	25	-0.020	0.7±0.3	0.5±0.3
	+0.035	24.990	1.475			0		-0.041		
MB2520DU	+0.075	25.071	1.505	20	28	+0.021	25	-0.020	0.7±0.3	0.5±0.3
	+0.035	24.990	1.475			0		-0.041		
MB2525DU	+0.075	25.071	1.505	25	28	+0.021	25	-0.020	0.7±0.3	0.5±0.3
	+0.035	24.990	1.475			0		-0.041		
MB2530DU	+0.075	25.071	1.505	30	28	+0.021	25	-0.020	0.7±0.3	0.5±0.3
	+0.035	24.990	1.475			0		-0.041		
MB2540DU	+0.075	25.071	1.505	40	28	+0.021	25	-0.020	0.7±0.3	0.5±0.3
	+0.035	24.990	1.475			0		-0.041		
MB2550DU	+0.075	25.071	1.505	50	28	+0.021	25	-0.020	0.7±0.3	0.5±0.3
	+0.035	24.990	1.475			0		-0.041		
MB2820DU	+0.085	28.085	2.005	20	32	+0.025	28	-0.020	1.2±0.4	0.5±0.3
	+0.045	27.990	1.970			0		-0.041		
MB2825DU	+0.085	28.085	2.005	25	32	+0.025	28	-0.020	1.2±0.4	0.5±0.3
	+0.045	27.990	1.970			0		-0.041		
MB3015DU	+0.085	30.085	2.005	15	34	+0.025	30	-0.020	1.2±0.4	0.5±0.3
	+0.045	29.990	1.970			0		-0.041		
MB3020DU	+0.085	30.085	2.005	20	34	+0.025	30	-0.020	1.2±0.4	0.5±0.3
	+0.045	29.990	1.970			0		-0.041		
MB3025DU	+0.085	30.085	2.005	25	34	+0.025	30	-0.020	1.2±0.4	0.5±0.3
	+0.045	29.990	1.970			0		-0.041		
MB3030DU	+0.085	30.085	2.005	30	34	+0.025	30	-0.020	1.2±0.4	0.5±0.3
	+0.045	29.990	1.970			0		-0.041		
MB3040DU	+0.085	30.085	2.005	40	34	+0.025	30	-0.020	1.2±0.4	0.5±0.3
	+0.045	29.990	1.970			0		-0.041		
MB3230DU	+0.085	32.085	2.005	30	36	+0.025	32	-0.025	1.2±0.4	0.5±0.3
	+0.045	31.990	1.970			0		-0.050		
MB3240DU	+0.085	32.085	2.005	40	36	+0.025	32	-0.025	1.2±0.4	0.5±0.3
	+0.045	31.990	1.970			0		-0.050		
MB3520DU	+0.085	35.085	2.005	20	39	+0.025	35	-0.025	1.2±0.4	0.5±0.3
	+0.045	34.990	1.970			0		-0.050		
MB3530DU	+0.085	35.085	2.005	30	39	+0.025	35	-0.025	1.2±0.4	0.5±0.3
	+0.045	34.990	1.970			0		-0.050		
MB3540DU	+0.085	35.085	2.005	40	39	+0.025	35	-0.025	1.2±0.4	0.5±0.3
	+0.045	34.990	1.970			0		-0.050		
MB3550DU	+0.085	35.085	2.005	50	39	+0.025	35	-0.025	1.2±0.4	0.5±0.3
	+0.045	34.990	1.970			0		-0.050		

DU Metric Cylindrical Bushes




Part No.	OD Tolerance	ID After Fitted	Wall Thickness	L +0.025 -0.025	Housing Bore (H7)	Shaft Dia (f7)	f1	f2			
MB4026DU	44	+0.085	40.085	2.005	26	44	+0.025	40	-0.025	1.2±0.4	0.5±0.3
		+0.045	39.990	1.970			0		-0.050		
MB4030DU	44	+0.085	40.085	2.005	30	44	+0.025	40	-0.025	1.2±0.4	0.5±0.3
		+0.045	39.990	1.970			0		-0.050		
MB4048DU	44	+0.085	40.085	2.005	48	44	+0.025	40	-0.025	1.2±0.4	0.5±0.3
		+0.045	39.990	1.970			0		-0.050		
MB4050DU	44	+0.085	40.085	2.005	50	44	+0.025	40	-0.025	1.2±0.4	0.5±0.3
		+0.045	39.990	1.970			0		-0.050		
MB4520DU	50	+0.085	45.105	2.505	20	50	+0.025	45	-0.025	1.8±0.6	0.6±0.3
		+0.045	44.990	2.460			0		-0.050		
MB4550DU	50	+0.085	45.105	2.505	50	50	+0.025	45	-0.025	1.8±0.6	0.6±0.3
		+0.045	44.990	2.460			0		-0.050		
MB5030DU	55	+0.100	50.110	2.505	30	55	+0.030	50	-0.025	1.8±0.6	0.6±0.3
		+0.055	49.990	2.460			0		-0.050		
MB5040DU	55	+0.100	50.110	2.505	40	55	+0.030	50	-0.025	1.8±0.6	0.6±0.3
		+0.055	49.990	2.460			0		-0.050		
MB5050DU	55	+0.100	50.110	2.505	50	55	+0.030	50	-0.025	1.8±0.6	0.6±0.3
		+0.055	49.990	2.460			0		-0.050		
MB5060DU	55	+0.100	50.110	2.505	60	55	+0.030	50	-0.025	1.8±0.6	0.6±0.3
		+0.055	49.990	2.460			0		-0.050		
MB6030DU	65	+0.100	60.110	2.505	30	65	+0.030	60	-0.030	1.8±0.6	0.6±0.3
		+0.055	59.990	2.460			0		-0.060		
MB6040DU	65	+0.100	60.110	2.505	40	65	+0.030	60	-0.030	1.8±0.6	0.6±0.3
		+0.055	59.990	2.460			0		-0.060		
MB6050DU	65	+0.100	60.110	2.505	50	65	+0.030	60	-0.030	1.8±0.6	0.6±0.3
		+0.055	59.990	2.460			0		-0.060		
MB6060DU	65	+0.100	60.110	2.505	60	65	+0.030	60	-0.030	1.8±0.6	0.6±0.3
		+0.055	59.990	2.460			0		-0.060		
MB6070DU	65	+0.100	60.110	2.505	70	65	+0.030	60	-0.030	1.8±0.6	0.6±0.3
		+0.055	59.990	2.460			0		-0.060		
MB6560DU	70	+0.100	65.110	2.505	60	70	+0.030	65	-0.030	1.8±0.6	0.6±0.3
		+0.055	64.990	2.460			0		-0.060		
MB6570DU	70	+0.100	65.110	2.505	70	70	+0.030	65	-0.030	1.8±0.6	0.6±0.3
		+0.055	64.990	2.460			0		-0.060		
MB7040DU	75	+0.100	70.110	2.505	40	75	+0.030	70	-0.030	1.8±0.6	0.6±0.3
		+0.055	69.990	2.460			0		-0.060		
MB7050DU	75	+0.100	70.110	2.505	50	75	+0.030	70	-0.030	1.8±0.6	0.6±0.3
		+0.055	69.990	2.460			0		-0.060		
MB7060DU	75	+0.100	70.110	2.505	60	75	+0.030	70	-0.030	1.8±0.6	0.6±0.3
		+0.055	69.990	2.460			0		-0.060		
MB7560DU	80	+0.100	75.110	2.505	60	80	+0.030	75	-0.030	1.8±0.6	0.6±0.3
		+0.055	74.990	2.460			0		-0.060		
MB8060DU	85	+0.120	80.155	2.490	60	85	+0.035	80	0	1.8±0.6	0.6±0.3
		+0.070	80.020	2.440			0		-0.046		
MB8080DU	85	+0.120	80.155	2.490	80	85	+0.035	80	0	1.8±0.6	0.6±0.3
		+0.070	80.020	2.440			0		-0.054		
MB80100DU	85	+0.120	80.155	2.490	100	85	+0.035	80	0	1.8±0.6	0.6±0.3
		+0.070	80.020	2.440			0		-0.054		
MB8560DU	90	+0.120	85.155	2.490	60	90	+0.035	85	0	1.8±0.6	0.6±0.3
		+0.070	85.020	2.440			0		-0.054		
MB9060DU	95	+0.120	90.155	2.490	60	95	+0.035	90	0	1.8±0.6	0.6±0.3
		+0.070	90.020	2.440			0		-0.054		
MB9560DU	100	+0.120	95.155	2.490	60	100	+0.035	95	0	1.8±0.6	0.6±0.3
		+0.070	95.020	2.440			0		-0.054		
MB95100DU	100	+0.120	95.155	2.490	100	100	+0.035	95	0	1.8±0.6	0.6±0.3
		+0.070	95.020	2.440			0		-0.054		
MB100115DU	105	+0.120	100.155	2.490	115	105	+0.035	100	0	1.8±0.6	0.6±0.3
		+0.070	100.020	2.440			0		-0.054		
MB10060DU	105	+0.120	100.155	2.490	60	105	+0.035	100	0	1.8±0.6	0.6±0.3
		+0.070	100.020	2.440			0		-0.054		
MB110115DU	115	+0.120	110.155	2.490	115	115	+0.035	110	0	1.8±0.6	0.6±0.3
		+0.070	110.020	2.440			0		-0.054		

Every effort has been taken to ensure that the data listed in this catalogue is correct. Finer Power Transmissions P/L will not accept liability for any damage or loss caused as a result of the data in this catalogue.

DU Metric Cylindrical Bushes

Part No.	OD Tolerance	ID After Fitted	Wall Thickness	L +0.025 -0.025	Housing Bore (H7)	Shaft Dia (f7)	f1	f2			
MB11570DU	120	+0.170	115.155	2.465	70	120	+0.035	115	0	1.8±0.6	0.6±0.3
		+0.100	115.020	2.415			0	-0.054			
MB120100DU	125	+0.170	120.210	2.465	100	125	+0.04	120	0	1.8±0.6	0.6±0.3
		+0.100	120.070	2.415			0		-0.054		
MB125100DU	130	+0.170	125.210	2.465	100	130	+0.04	125	0	1.8±0.6	0.6±0.3
		+0.100	125.070	2.415			0		-0.063		
MB130100DU	135	+0.170	130.210	2.465	100	135	+0.04	130	0	1.8±0.6	0.6±0.3
		+0.100	130.070	2.415			0		-0.063		
MB145100DU	150	+0.170	145.210	2.465	100	150	+0.04	145	0	1.8±0.6	0.6±0.3
		+0.100	145.020	2.415			0		-0.063		
MB150100DU	155	+0.170	150.210	2.465	100	155	+0.04	150	0	1.8±0.6	0.6±0.3
		+0.100	150.020	2.415			0		-0.063		
MB155100DU	160	+0.170	150.210	2.465	100	160	+0.04	155	0	1.8±0.6	0.6±0.3
		+0.100	150.020	2.415			0		-0.063		
MB16060DU	165	+0.170	160.210	2.465	60	165	+0.04	160	0	1.8±0.6	0.6±0.3
		+0.100	160.020	2.415			0		-0.063		
MB160100DU	165	+0.170	160.210	2.465	100	165	+0.04	160	0	1.8±0.6	0.6±0.3
		+0.100	160.020	2.415			0		-0.063		
MB165100DU	170	+0.170	165.210	2.465	100	170	+0.04	165	0	1.8±0.6	0.6±0.3
		+0.100	165.020	2.415			0		-0.063		
MB170100DU	175	+0.170	170.210	2.465	100	175	+0.04	170	0	1.8±0.6	0.6±0.3
		+0.100	170.020	2.415			0		-0.063		
MB175100DU	180	+0.170	175.210	2.465	100	180	+0.04	175	0	1.8±0.6	0.6±0.3
		+0.100	175.020	2.415			0		-0.063		
MB200100DU	205	+0.210	200.216	2.465	100	205	+0.046	200	0	1.8±0.6	0.6±0.3
		+0.130	200.070	2.415			0		-0.072		
MB220100DU	225	+0.210	220.216	2.465	100	225	+0.046	220	0	1.8±0.6	0.6±0.3
		+0.130	220.070	2.415			0		-0.072		
MB250100DU	255	+0.260	250.222	2.465	100	255	+0.052	250	0	1.8±0.6	0.6±0.3
		+0.170	250.070	2.415			0		-0.072		
MB300100DU	305	+0.260	300.222	2.465	100	305	+0.052	300	0	1.8±0.6	0.6±0.3
		+0.170	300.070	2.415			0		-0.081		

DX Imperial Cylindrical Bushes (Lined)



Unit: Inch

Part No.	Nominal Diameter		L	ID After Fitted	Shaft Dia (f7)	Housing Bore (H7)	f1	f2	z
	D	d							
IB12DX12	7/8	3/4	3/4	0.7444	0.7390	0.8758	5/32	0.7±0.3	0.5±0.2
				0.7412	0.7378	0.8750			
IB12DX16	7/8	3/4	1	0.7444	0.7390	0.8758	5/32	0.7±0.3	0.5±0.2
				0.7412	0.7378	0.8750			
IB16DX16	1.1/8	1	1	0.9944	0.9888	1.1258	1/4	0.7±0.3	0.5±0.2
				0.9912	0.9876	1.1250			
IB24DX16	1.21/32	1.1/2	1	1.4952	1.4884	1.6572	5/16	0.7±0.4	0.5±0.3
				1.4914	1.4868	1.6562			

DX Metric Cylindrical Bushes (Lined)

Part No.	OD Tolerance		ID After Fitted	Wall Thickness	L +0.025 -0.025	Housing Bore (H7)	Shaft Dia (f7)	Oil hole (H)	f1	f2
MB1625DX	18	+0.065	16.108	0.980	25	18 +0.018	16 0	4	0.6±0.3	0.3±0.2
		+0.030	16.040	0.955		0	-0.027			
MB3530DX	39	+0.085	35.155	1.970	30	39 +0.025	35 0	6	1.2±0.4	0.5±0.2
		+0.045	35.060	1.935		0	-0.039			
MB3550DX	39	+0.085	35.155	1.970	50	39 +0.025	35 0	6	1.2±0.4	0.5±0.2
		+0.046	35.060	1.935		0	-0.039			
MB6040DX	65	+0.100	60.200	2.460	40	65 +0.03	60 0	8	1.8±0.6	0.6±0.2
		+0.055	60.080	2.415		0	-0.046			
MB6060DX	65	+0.100	60.200	2.460	60	65 +0.03	60 0	8	1.8±0.6	0.6±0.2
		+0.056	60.080	2.415		0	-0.046			
MB80100DX	85	+0.120	80.265	2.450	100	85 +0.035	80 0	9.5	1.8±0.6	0.6±0.2
		+0.070	80.100	2.385		0	-0.046			
MB8060DX	85	+0.120	80.265	2.450	60	85 +0.035	80 0	9.5	1.8±0.6	0.6±0.2
		+0.071	80.100	2.385		0	-0.046			
MB8080DX	85	+0.120	80.265	2.450	80	85 +0.035	80 0	9.5	1.8±0.6	0.6±0.2
		+0.073	80.100	2.385		0	-0.046			