


SY ANSI straight sidebar chains are identical with ANSI standard chains except for the straight side plates. Provided with higher fatigue resistance than the standard chains.

Sprockets for ANSI standard chains may be used for these chains. For identification, a suffix of F is added to the standard chain numbers as listed below.



SY Chain No. (ANSI)	Dimensions - mm										Minimum Ultimate Strength	Maximum Allowable Load	Average Chain Weight	Type of Conn link
	Pitch	Roller		Pin				Plate						
		Width	Dia.	Dia.	Length			Height	Thick.					
		P	W	R	D	LR	LC	L1	L2	H				
35F	9.525	4.78	5.08	3.58	12.0	12.9	6.0	6.9	9.0	1.25	10.8	2.23	0.38	Spcl
40F	12.7	7.95	7.92	3.96	16.5	17.7	8.3	9.4	11.7	1.5	19.1	4.17	0.67	-
50F	15.875	9.53	10.16	5.08	20.4	21.9	10.2	11.7	14.6	2	31.9	7.22	1.1	-
60F	19.05	12.7	11.91	5.95	25.5	26.9	12.8	14.1	17.5	2.4	43.1	10.7	1.63	-
80F	25.4	15.88	15.88	7.93	32.8	35.0	16.4	18.6	23.4	3.2	78.5	18.4	2.82	C
100F	31.75	19.05	19.05	9.53	39.4	43.0	19.7	23.3	29.3	4.0	118	28.3	4.37	-
120F	38.1	25.4	22.23	11.1	49.5	53.4	24.8	28.6	35.1	4.8	167	38	6.45	-
140F	44.45	25.4	25.4	12.7	54.0	58.3	27.0	31.3	40.9	5.6	216	50.3	8.29	-
160F	50.8	31.75	28.58	14.28	65.3	68.7	32.2	36.5	46.7	6.4	275	66.3	103.96	-
200F	63.5	38.1	39.67	19.83	78.5	87.0	39.3	47.7	59.8	8.0	451	82.3	18.96	-
240F	76.2	47.63	47.63	23.78	96.4	104.1	48.2	55.9	70.3	9.5	677	112.8	26.47	-