FYH Finer Power Transmissions P/L | www.finerpt.com

Bearing Inserts

NA200 Triple Lip Series



NA

NA200 Triple Lip Series



NA

Shaft Dia		Dimensions										Basic Load ratings kN		Factor	Bearing no.		Dimensions								Set Screw Brg. Bore		Mass kg
mm	inch	D		B		B1		C		r (min.)							C1		S		S2		d1		G		
d		mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	Cr	C0r	f 0			mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	
	3/4	47	1.85	34.2	1.346	43.7	1.72	16	0.63	1	0.039	12.8	6.65	13.2	NA204-12L2		4	0.157	17.1	0.673	4.8	0.189	33.3	1.311	–	1/4-28UNF	0.23
20		47	1.85	34.2	1.346	43.7	1.72	16	0.63	1	0.039	12.8	6.65	13.2	NA204L2		4	0.157	17.1	0.673	4.8	0.189	33.3	1.311	M6×0.75	–	0.22
-	7/8	52	2.047	34.9	1.374	44.4	1.748	17	0.669	1	0.039	14	7.85	13.9	NA205-14L2		5	0.197	17.5	0.689	4.8	0.189	38.1	1.5	-	1/4-28UNF	0.27
	15/16	52	2.047	34.9	1.374	44.4	1.748	17	0.669	1	0.039	14	7.85	13.9	NA205-15L2		5	0.197	17.5	0.689	4.8	0.189	38.1			1/4-28UNF	0.29
	1	52	2.047	34.9	1.374	44.4	1.748	17	0.669	1	0.039	14	7.85	13.9	NA205-16L2		5	0.197	17.5	0.689	4.8	0.189	38.1	1.5	–	1/4-28UNF	0.25
25		52	2.047	34.9	1.374	44.4	1.748	17	0.669	1	0.039	14	7.85	13.9	NA205L2		5	0.197	17.5	0.689	4.8	0.189	38.1	1.5	M6×0.75	–	0.25
	1 1/16	62	2.441	36.5	1.437	48.4	1.906	19	0.748	1	0.039	19.5	11.3	13.9	NA206-17L3		5	0.197	18.3	0.72	6	0.236	44.5	1.752	-	-	-
	1 1/8	62	2.441	36.5	1.437	48.4	1.906	19	0.748	1	0.039	19.5	11.3	13.9	NA206-18L3		5	0.197	18.3	0.72	6	0.236	44.5	1.752	–	5/16-24UNF	0.43
	1 3/16	62	2.441	36.5	1.437	48.4	1.906	19	0.748	1	0.039	19.5	11.3	13.9	NA206-19L3		5	0.197	18.3	0.72	6	0.236	44.5	1.752	–	5/16-24UNF	0.41
	1 1/4	62	2.441	36.5	1.437	48.4	1.906	19	0.748	1	0.039	19.5	11.3	13.9	NA206-20L3		5	0.197	18.3	0.72	6	0.236	44.5	1.752	–	5/16-24UNF	0.38
30		62	2.441	36.5	1.437	48.4	1.906	19	0.748	1	0.039	19.5	11.3	13.9	NA206L3		5	0.197	18.3	0.72	6	0.236	44.5	1.752	M8×1	–	0.41
	1 1/4	72	2.835	37.6	1.48	51.1	2.012	20	0.787	1.1	0.043	25.7	15.4	13.9	NA207-20L3		5.5	0.217	18.8	0.74	6.8	0.268	55.6	2.189	–	5/16-24UNF	0.68
	1 5/16	72	2.835	37.6	1.48	51.1	2.012	20	0.787	1.1	0.043	25.7	15.4	13.9	NA207-21L3		5.5	0.217	18.8	0.74	6.8	0.268	55.6	2.189	-	5/16-24UNF	0.65
	1 3/8	72	2.835	37.6	1.48	51.1	2.012	20	0.787	1.1	0.043	25.7	15.4	13.9	NA207-22L3		5.5	0.217	18.8	0.74	6.8	0.268	55.6	2.189	–	5/16-24UNF	0.61
	1 7/16	72	2.835	37.6	1.48	51.1	2.012	20	0.787	1.1	0.043	25.7	15.4	13.9	NA207-23L3		5.5	0.217	18.8	0.74	6.8	0.268	55.6	2.189	–	5/16-24UNF	0.58
35		72	2.835	37.6	1.48	51.1	2.012	20	0.787	1.1	0.043	25.7	15.4	13.9	NA207L3		5.5	0.217	18.8	0.74	6.8	0.268	55.6	2.189	M8×1	–	0.61
	1 1/2	80	3.15	42.8	1.685	56.3	2.217	21	0.827	1.1	0.043	29.1	17.8	14	NA208-24L3		6	0.236	21.4	0.843	6.8	0.268	60.3	2.374	–	5/16-24UNF	0.83
	1 9/16	80	3.15	42.8	1.685	56.3	2.217	21	0.827	1.1	0.043	29.1	17.8	14	NA208-25L3		6	0.236	21.4	0.843	6.8	0.268	60.3	2.374	-	5/16-24UNF	0.79
40		80	3.15	42.8	1.685	56.3	2.217	21	0.827	1.1	0.043	29.1	17.8	14	NA208L3		6	0.236	21.4	0.843	6.8	0.268	60.3	2.374	M8×1	–	0.78
	1 5/8	85	3.346	42.8	1.685	56.3	2.217	22	0.866	1.1	0.043	34.1	21.3	14	NA209-26L3		6	0.236	21.4	0.843	6.8	0.268	63.5	2.5	–	5/16-24UNF	0.96
	1 11/16	85	3.346	42.8	1.685	56.3	2.217	22	0.866	1.1	0.043	34.1	21.3	14	NA209-27L3		6	0.236	21.4	0.843	6.8	0.268	63.5	2.5	–	5/16-24UNF	0.91
	1 3/4	85	3.346	42.8	1.685	56.3	2.217	22	0.866	1.1	0.043	34.1	21.3	14	NA209-28L3		6	0.236	21.4	0.843	6.8	0.268	63.5	2.5	–	5/16-24UNF	0.87
45		85	3.346	42.8	1.685	56.3	2.217	22	0.866	1.1	0.043	34.1	21.3	14	NA209L3		6	0.236	21.4	0.843	6.8	0.268	63.5	2.5	M8×1	–	0.85
	1 7/8	90	3.543	49.2	1.937	62.7	2.469	24	0.945	1.1	0.043	35.1	23.3	14.4	NA210-30L3		6	0.236	24.6	0.969	6.8	0.268	69.9	2.752	–	5/16-24UNF	1.08
	1 15/16	90	3.543	49.2	1.937	62.7	2.469	24	0.945	1.1	0.043	35.1	23.3	14.4	NA210-31L3		6	0.236	24.6	0.969	6.8	0.268	69.9	2.752	-	5/16-24UNF	1.04
	2	90	3.543	49.2	1.937	62.7	2.469	24	0.945	1.1	0.043	35.1	23.3	14.4	NA210-32L3		6	0.236	24.6	0.969	6.8	0.268	69.9	2.752	-	5/16-24UNF	0.99
50		90	3.543	49.2	1.937	62.7	2.469	24	0.945	1.1	0.043	35.1	23.3	14.4	NA210L3		6	0.236	24.6	0.969	6.8	0.268	69.9	2.752	M8×1	–	1.01
	2	100	3.937	55.5	2.185	71.4	2.811	25	0.984	1.5	0.059	43.4	29.4	14.4	NA211-32L3		7	0.276	27.8	1.094	8	0.315	76.2	3	–	3/8-24UNF	1.58
	2 1/8	100	3.937	55.5	2.185	71.4	2.811	25	0.984	1.5	0.059	43.4	29.4	14.4	NA211-34L3		7	0.276	27.8	1.094	8	0.315	76.2	3	M10x1.25	-	1.39
	2 3/16	100	3.937	55.5	2.185	71.4	2.811	25	0.984	1.5	0.059	43.4	29.4	14.4	NA211-35L3		7	0.276	27.8	1.094	8	0.315	76.2	3	-	3/8-24UNF	1.36
55		100	3.937	55.5	2.185	71.4	2.811	25	0.984	1.5	0.059	43.4	29.4	14.4	NA211L3		7	0.276	27.8	1.094	8	0.315	76.2	3	M10×1.25	–	1.39
	2 1/4	110	4.331	61.9	2.437	77.8	3.063	27	1.063	1.5	0.059	52.4	36.2	14.4	NA212-36L3		7.5	0.295	31	1.22	8	0.315	84.2	3.315	–	3/8-24UNF	2.03
	2 3/8	110	4.331	61.9	2.437	77.8	3.063	27	1.063	1.5	0.059	52.4	36.2	14.4	NA212-38L3		7.5	0.295	31	1.22	8	0.315	84.2	3.315	-	-	-
	2 7/16	110	4.331	61.9	2.437	77.8	3.063	27	1.063	1.5	0.059	52.4	36.2	14.4	NA212-39L3		7.5	0.295	31	1.22	8	0.315	84.2	3.315	-	-	-
60		110	4.331	61.9	2.437	77.8	3.063	27	1.063	1.5	0.059	52.4	36.2	14.4	NA212L3		7.5	0.295	31	1.22	8	0.315	84.2	3.315	M10×1.25	–	1.87

Note: L2 = Double Lip, L3 = Triple Lip

BOOK 7: BEARINGS – KOYO

7.2 PREMIUM FYH BEARINGS

Every effort has been taken to ensure that the data listed in this catalogue is correct.
Finer Power Transmissions P/L will not accept liability for any damage or loss caused as a result of the data in this catalogue.

Every effort has been taken to ensure that the data listed in this catalogue is correct.
Finer Power Transmissions P/L will not accept liability for any damage or loss caused as a result of the data in this catalogue.