

Protective Coatings



Your Application

- Protect, seal, insulate, prevent corrosion, add gripping power and color code tools
- Provide excellent resistance to acids, alkalis, salt and moisture, which can damage equipment

SURFACE PROTECTION AND RUST PREVENTION

Corrosion Protection

General-Purpose

Cathodic Protection

Undercoating

Non-Drying

Color Coding

SF 7693™

SF 7607™

PC 9660™

SF F720™

Solution

Description	Zinc Spray	Rubberized Spray	Wax Film	Rubber Coating
Color	Grey	Black	Brown	Red, Yellow, Blue, Black
Temperature Range	Up to 400°F (204°C)	Up to 200°F (93°C)	Up to 200°F (93°C)	Up to 200°F (93°C)
Cure/Dry Time	15 min.	20 min.	N/A	4 hrs.

Product Description

LOCTITE® SF 7693™ Cold Galvanizing Compound

Sprays on metal surfaces to prevent corrosion even when the surface is scratched. Ideal touch-up for welded seams. Highly resistant to salt corrosion and water. Not resistant to acid or alkaline solutions. Contains no ozone-depleting compounds. Won't yellow, chalk or peel.

P/N Package Size
82039 15 oz. net wt. aerosol

LOCTITE® SF 7607™ Heavy-Duty Rubberized Undercoating

This heavy-duty undercoating seals, protects and insulates. Rubberized for maximum durability. Features abrasion resistance and sound-deadening properties.

P/N Package Size
30538 16 oz. net wt. aerosol

LOCTITE® PC 9660™ Heavy-Duty Rustproofing

Heavy-duty coating provides long-term protection for metal parts, equipment and machinery. Forms a protective, waxy film that seals out moisture, air, acid and other corrosive elements. Great for protecting parts in storage. Removable with LOCTITE® Electrical Contact Cleaner.

P/N Package Size
51211 12 oz. net wt. aerosol
51213 1 gallon can

LOCTITE® SF F720™ Tough Rubber Coating

Inhibits Rust and Corrosion, Seals, Insulates and Identifies

A solvent-based, modified thermoplastic liquid coating that dries to a durable, flexible, rubber-like protective coating on parts and equipment. Dip, spray or brush to apply. Great for tools, metals, electrical connections, masonry, wood, conveyors, glass, rope and fabric.

P/N Package Size
34979 14.5 fl. oz. can, black
34980 1 gallon can, black
34982 14.5 fl. oz. can, blue
34983 1 gallon can, blue
34985 14.5 fl. oz. can, red
34988 14.5 fl. oz. can, yellow
34989 1 gallon can, yellow

COATING HINTS

- When coating any surface, make sure the parts are clean and dry. Try doing a small test piece first to confirm that the coating meets your expectations. This will save you time and money if the desired results are not achieved.
- LOCTITE® SF F720™ Thinner can be used to remove cured LOCTITE® SF F720™ Coating.
- LOCTITE® SF F720™ Coating colors can be mixed to make different colors.

HELPFUL HINTS