Solvent-Based & Specialty Adhesives



Your Application

To meet tough onthe-job requirements, LOCTITE® solvent-based aerosol and liquid adhesives provide a combination of:

- · Cure speed
- Impact resistance
- Strength
- Temperature range
- Solvent and moisture resistance

Solution

WHAT TYPE OF APPLICATION PROCESS WOULD YOU PREFER? **Liquid Tube Application Aerosol Spray** Temperature Extremes, **Quick Early Maximum** Gasoline and Solvent-Free **All-Purpose** Strength Strength Kerosene Resistant Power Grab® Industrial MR 5414[™] MR 5412™ MR 5416™ MR 5426™ Construction **Adhesive** Color Black Yellow Clear Clear Clear Up to 180°F Up to 180°F Up to 120°F Up to 170°F Up to 120°F **Temperature Range** (82°C) (82°C) (49°C) (77°C) (49°C) **Fixture Time (min.)** 2 to 3 2 to 3 20 15 to 20 15 to 20

Product Description

Agency Approvals

LOCTITE® MR 5414™ **Black Contact Adhesive**

CFIA Listed

A professional, solventbased adhesive with neoprene that blends in with black-colored fabrics, rubbers, weather stripping and other porous materials. Withstands temperature extremes and is resistant to gasoline, kerosene and other solvents. Fast drying and waterproof. Allows repositioning of the parts after initial contact.

Package Size 30540 5 fl. oz. tube - Black

LOCTITE® MR 5412™ **Contact Adhesive**

CFIA Listed

A fast drying, solventbased adhesive with neoprene that bonds rubber, insulation, weather stripping and other porous materials. Sets to a tack-free surface in 3-4 minutes, and the early strength is enough to hold most parts together. Allows repositioning of the parts after initial contact.

P/N Package Size 30537 5 fl. oz. tube - Yellow

LOCTITE® Power Grab® Industrial Construction Adhesive

N/A

Single-component, off-white, heavy duty, high strength, construction grade adhesive for interior and exterior repairs or building projects.

P/N Package Size 1804373 300 ml cartridge

LOCTITE® MR 5426™ **Maximum Strength Headliner Adhesive**

N/A

A high strength, aerosol product designed for bonding foam, carpet, fabrics, plastics, rubber, etc. LOCTITE® Maximum Strength Headliner Adhesive is resistant to extreme seasonal temperatures, is water resistant and sprays on clear.

Package Size 37312 16.75 oz. net wt.

LOCTITE® MR 5416™ **All Purpose Spray Adhesive**

N/A

Bonds lightweight, porous and nonporous surfaces. Allows for repositionable and permanent bonds. Fast drying; won't shrink or bleed. Resists water and humidity. Contains no ozone-depleting compounds.

P/N Package Size 30544 10.5 oz. net wt. aerosol