

## 5542 Pipe Sealant

Medium viscosity, high-strength pipe sealant well penetrating into fine threads, resisting up to  $-50^{\circ}\text{C}$  /  $+200^{\circ}\text{C}$ . Solvent-free. Non-dripping. When fully cured, will seal up to the bursting pressure of the pipe. Seals anaerobically. Keeps its strength and sealing properties against shocks & vibrations long after application. Used on close-fitting metal pipe threads where all kinds of water, oil, grease, and chemicals pass. Can also be used in assembling joint parts of pressure vessels, air compressors, hydraulic systems and tanks, and in areas where resistance against vibration is required.

Suitable for Type H thick metal thread joints according to TSE EN 751-1 Standard.



PART NO.	BOTTLE SIZE	BOX QTY
5542-050ML	50ml	10
5542-250ML	250ml	6

## 5543 Pipe Sealant

General purpose, medium-viscosity, medium-strength, removable, oil-resistant pipe sealant. Resists up to  $-50^{\circ}\text{C}$  /  $+150^{\circ}\text{C}$ . Solvent-free. Non-dripping.

When fully cured, seals up to the bursting pressure of the pipe. Seals anaerobically. Keeps its strength and sealing properties against shocks & vibrations long after application. Used on close-fitting metal pipe threads where all kinds of water, oil, grease, and chemicals pass. Can also be used in compressors, hydraulic systems and tanks, and in areas where resistance against vibration is required.

Suitable for Type H thick metal thread joints according to TSE EN 751-1 Standard.



PART NO.	BOTTLE SIZE	BOX QTY
5543-050ML	50ml	10
5543-250ML	250ml	6