

# Hydraulic Hose

Finer Power Transmissions stocks a range of Ag Flex 1 wire and 2 wire braided hydraulic hoses. It is generally suitable for medium to high pressure hydraulic lines, suitable for petroleum based hydraulic fluids, synthetic esters and biogrdragable hydraulic fluids.

## 1 Wire Braid Hose - EN853 1SN



Part No.	Hose Size		Braid Diameter (mm)	Hose OD (mm)	Reel Length (M)
	DIN	IMP			
R1AT1/4-1SN06	6	1/4	10.8-11.4	12.7-13.5	100
R1AT3/8-1SN10	10	3/8	14.5-15.1	16.7-17.5	100
R1AT1/2-1SN12	12	1/2	17.7-18.3	19.8-20.6	100
R1AT5/8-1SN16	16	5/8			
R1AT3/4-1SN20	20	3/4	24.6-25.4	26.9-27.7	50
R1AT1-1SN25	25	1	32.1-32.9	34.6-35.4	

## 2 Wire Braid Hose - EN853 2SN



Part No.	Hose Size		Braid Diameter (mm)	Hose OD (mm)	Reel Length (M)
	DIN	IMP			
R2AT1/4-2SN06	6	1/4	12.5-13.1	14.4-15.2	100
R2AT3/8-2SN10	10	3/8	16.2-16.8	18.3-19.1	100
R2AT1/2-2SN12	12	1/2	19.4-20.0	19.8-20.6	100
R2AT5/8-2SN16	16	5/8			
R2AT3/4-2SN20	20	3/4	26.4-27.2	28.6-29.4	50
R2AT1-2SN25	25	1	33.9-24.7	36.5-37.1	

Liner: Synthetic oil resistant rubber

Reinforcement: High tensile steel braid

Working Temperature: -40°C to +100°C

Intermittent Temperature: -40°C to +120°C