

14M HTD Timing Pulleys (Taper Lock)

Size	Z	Mat	Bush	Outside Dia.	Hub Dia.	W	d3	Max. Bore
28-14M-40	28	GG	2012	122.12	127	54	-	50
28-14M-55	28	GG	2012	122.12	127	70	-	50
28-14M-85	28	GG	2517	122.12	127	102	-	60
28-14M-115	28	GG	2517	122.12	127	133	-	60
29-14M-40	29	GG	2012	126.57	138	54	-	50
29-14M-55	29	GG	2012	126.57	138	70	-	50
29-14M-85	29	GG	2517	126.57	138	102	-	60
29-14M-115	29	GG	2517	126.57	138	133	-	60
30-14M-40	30	GG	2012	130.99	138	54	-	50
30-14M-55	30	GG	2517	130.99	138	70	-	60
30-14M-85	30	GG	2517	130.99	138	102	-	60
30-14M-115	30	GG	2517	130.99	138	133	-	60
32-14M-40	32	GG	2012	139.88	154	54	-	50
32-14M-55	32	GG	2517	139.88	154	70	-	60
32-14M-85	32	GG	2517	139.88	154	102	-	60
32-14M-115	32	GG	2517	139.88	154	133	-	60
34-14M-40	34	GG	2517	148.79	160	54	-	60
34-14M-55	34	GG	2517	146.79	160	70	-	60
34-14M-85	34	GG	2517	146.79	160	102	-	60
34-14M-115	34	GG	2517	146.79	160	133	-	60
36-14M-40	36	GG	2517	157.68	168	54	-	60
36-14M-55	36	GG	2517	157.68	168	70	-	60
36-14M-85	36	GG	3020	157.68	168	102	-	75
36-14M-115	36	GG	3020	157.68	168	133	-	75
38-14M-40	38	GG	2517	166.6	183	54	-	60
38-14M-55	38	GG	2517	166.6	183	70	-	60
38-14M-85	38	GG	3020	166.6	183	102	-	75
38-14M-115	38	GG	3020	166.6	183	133	-	75
40-14M-40	40	GG	2517	175.49	188	54	-	60
40-14M-55	40	GG	2517	175.49	188	70	-	60
40-14M-85	40	GG	3020	175.49	188	102	-	75
40-14M-115	40	GG	3020	175.49	188	133	-	75
44-14M-40	44	GG	3020	193.28	211	54	-	75
44-14M-55	44	GG	3020	293.28	211	70	-	75
44-14M-85	44	GG	3030	293.28	211	102	-	75
44-14M-115	44	GG	3030	293.28	211	133	-	75
48-14M-40	48	GG	3020	211.11	226	54	-	75
48-14M-55	48	GG	3020	211.11	226	70	-	75
48-14M-85	48	GG	3030	211.11	226	102	-	75
48-14M-115	48	GG	3030	211.11	226	133	-	75
56-14M-40	56	GG	3020	246.76	256	54	170	75
56-14M-55	56	GG	3020	246.76	256	70	170	75
56-14M-85	56	GG	3535	246.76	256	102	190	90
56-14M-115	56	GG	3535	246.76	256	133	-	90
64-14M-40	64	GG	3020	282.41	296	54	170	75
64-14M-55	64	GG	3020	282.41	296	70	170	75
64-14M-85	64	GG	3525	282.41	296	102	190	90
64-14M-115	64	GG	3535	282.41	296	133	190	90
72-14M-40	72	GG	3020	318.06	-	54	170	75
72-14M-55	72	GG	3020	318.06	-	70	170	75
72-14M-85	72	GG	3535	318.06	-	102	190	90
72-14M-115	72	GG	3535	318.06	-	133	190	90
80-14M-40	80	GG	3535	353.71	-	133	190	90
80-14M-55	80	GG	3020	353.71	-	70	170	75
80-14M-85	80	GG	3525	353.71	-	102	190	90
80-14M-115	80	GG	3535	353.71	-	133	190	90

Table continue next page.

14M HTD Timing Pulleys (Taper Lock)

Size	Z	Mat	Bush	Outside Dia.	Hub Dia.	W	d3	Max. Bore
90-14M-40	90	GG	3020	398.28	-	54	170	75
90-14M-55	90	GG	3020	398.28	-	70	170	75
90-14M-85	90	GG	3525	398.28	-	89	190	90
90-14M-115	90	GG	3535	398.28	-	133	190	90
112-14M-40	112	GG	3020	496.32	-	54	170	75
112-14M-55	112	GG	3020	496.32	-	70	170	75
112-14M-85	112	GG	3525	496.32	-	70	170	75
112-14M-115	112	GG	3535	496.32	-	133	190	90
144-14M-40	144	GG	3020	638.92	-	54	170	75
144-14M-55	144	GG	3020	638.92	-	70	170	75
144-14M-85	144	GG	3535	638.92	-	102	190	90
144-14M-115	144	GG	4040	638.92	-	133	230	100
168-14M-40	168	GG	3020	745.87	-	54	170	75
168-14M-55	168	GG	3020	745.87	-	70	170	75
168-14M-85	168	GG	3525	745.87	-	89	190	90
168-14M-115	168	GG	4040	745.87	-	133	230	100
192-14M-40	192	GG	3020	852.82	-	54	170	75
192-14M-55	192	GG	3020	852.82	-	70	170	75
192-14M-85	192	GG	4040	852.82	-	102	230	100
192-14M-115	192	GG	4040	852.82	-	133	230	100
216-14M-40	216	GG	3020	959.76	-	54	170	75
216-14M-55	216	GG	3535	959.76	-	-	-	-
216-14M-85	216	GG	4040	959.76	-	102	230	100
216-14M-115	216	GG	4040	959.76	-	133	230	100