

8M HTD Timing Pulleys (Taper Lock)

Size	Z	Mat	Bush	Outside Dia.	Hub Dia.	W	d3	Max. Bore
22-8M-20	22	GG	1008/1108	54.65	60.0	28.0	-	25
22-8M-30	22	GG	1008/1108	54.65	60.0	38.0	-	25
24-8M-20	24	GG	1108	59.75	66.0	28.0	-	28
24-8M-30	24	GG	1108	59.75	66.0	38.0	-	28
26-8M-20	26	GG	1108	64.84	71.0	28.0	-	28
26-8M-30	26	GG	1108	64.84	71.0	38.0	-	28
28-8M-20	28	GG	1108	70.08	75.0	28.0	-	28
28-8M-30	28	GG	1210	70.08	75.0	38.0	-	35
28-8M-50	28	GG	1210	70.08	75.0	60.0	-	35
30-8M-20	30	GG	1108	75.13	83.0	28.0	-	28
30-8M-30	30	GG	1615	75.13	83.0	38.0	-	42
30-8M-50	30	GG	1615	75.13	83.0	60.0	-	42
32-8M-20	32	GG	1610	80.16	87.0	28.0	-	42
32-8M-30	32	GG	1615	80.16	87.0	38.0	-	42
32-8M-50	32	GG	1615	80.16	87.0	60.0	-	42
32-8M-85	32	GG	1615	80.16	87.0	95.0	-	42
34-8M-20	34	GG	1610	85.22	91.0	28.0	-	42
34-8M-30	34	GG	1610	85.22	91.0	28.0	-	42
34-8M-50	34	GG	1615	85.22	91.0	60.0	-	42
34-8M-85	34	GG	1615	85.22	91.0	95.0	-	42
36-8M-20	36	GG	1610	90.30	98.5	28.0	-	42
36-8M-30	36	GG	1615	90.30	98.5	38.0	-	42
36-8M-50	36	GG	1615	95.39	103.0	60.0	-	42
36-8M-85	36	GG	1615	90.35	98.5	95.0	-	42
38-8M-20	38	GG	1610	95.39	103.0	28.0	-	42
38-8M-30	38	GG	1615	95.39	103.0	38.0	-	42
38-8M-50	38	GG	1615	95.39	103.0	60.0	-	42
38-8M-85	38	GG	1615	95.39	103.0	95.0	-	42
40-8M-20	40	GG	1610	100.49	106.0	28.0	-	42
40-8M-30	40	GG	1615	100.49	106.0	38.0	-	42
40-8M-50	40	GG	2012	100.49	106.0	60.0	-	50
40-8M-85	40	GG	2012	100.49	106.0	95.0	-	50
44-8M-20	44	GG	2012	110.67	119.0	28.0	-	50
44-8M-30	44	GG	2012	110.67	119.0	38.0	-	50
44-8M-50	44	GG	2012	110.67	119.0	60.0	-	50
44-8M-85	44	GG	2012	110.67	119.0	95.9	-	50
48-8M-20	48	GG	2012	120.86	127.0	28.0	96	50
48-8M-30	48	GG	2012	120.86	127.0	38.0	-	50
48-8M-50	48	GG	2012	120.86	127.0	60.0	-	50
48-8M-85	48	GG	2517	120.86	127.0	95.0	-	60
56-8M-20	56	GG	2012	141.23	148.0	28.0	110	50
56-8M-30	56	GG	2012	141.23	148.0	38.0	-	50
56-8M-50	56	GG	2517	141.23	148.0	60.0	-	60
56-8M-85	56	GG	2517	120.86	127.0	95.0	-	60
64-8M-20	64	GG	2012	161.60	168.0	28.0	110	50

Table continue next page.

8M HTD Timing Pulleys (Taper Lock)

Size	Z	Mat	Bush	Outside Dia.	Hub Dia.	W	d3	Max. Bore
64-8M-30	64	GG	2517	161.60	168.0	38.0	125	60
64-8M-50	64	GG	2517	161.60	168.0	60.0	-	60
64-8M-85	64	GG	2517	161.60	168.0	95.0	-	60
72-8M-20	72	GG	2012	181.97	192.0	28.0	110	50
72-8M-30	72	GG	2517	181.97	192.0	38.0	125	60
72-8M-50	72	GG	2517	181.97	192.0	60.0	125	60
72-8M-85	72	GG	3020	181.97	192.0	95.0	-	75
80-8M-20	80	GG	2012	202.35	-	28.0	110	50
80-8M-30	80	GG	2517	202.35	-	38.0	125	60
80-8M-50	80	GG	3020	202.35	-	60.0	-	75
80-8M-85	80	GG	3020	202.35	-	95.0	-	75
90-8M-20	90	GG	2012	227.81	-	28.0	110	50
90-8M-30	90	GG	2517	227.81	-	38.0	125	60
90-8M-50	90	GG	3020	227.81	-	60.0	170	75
90-8M-85	90	GG	3020	227.81	-	95.0	170	75
112-8M-30	112	GG	2517	283.83	-	38.0	125	60
112-8M-50	112	GG	3020	283.83	-	60.0	170	75
112-8M-85	112	GG	3020	283.83	-	95.0	170	75
144-8M-30	144	GG	2517	365.32	-	38.0	125	60
144-8M-50	144	GG	3020	365.32	-	60.0	170	75
144-8M-85	144	GG	3525	365.32	-	95.0	190	90
168-8M-50	168	GG	3020	426.44	-	60.0	190	90
168-8M-85	168	GG	3525	426.44	-	95.0	190	90
192-8M-50	192	GG	3525	487.55	-	60.0	190	90
192-8M-85	192	GG	3525	487.55	-	95.0	190	90